



दुल्लू नगरपालिका
नगर कार्यपालिकाको कार्यालय



पत्र संख्या २०८२/०८३
चलानी नं :-



मिति: २०८२/१०/२३

बिषय : दर रेट पेश गर्ने सम्बन्धमा।

श्री जो जस सँग सम्बन्धित छ।

उपरोक्त विषयमा यस दुल्लू नगरपालिकाको चालू आ.व. २०८२।८३ को स्वीकृत कार्यक्रमहरूका लागि यससाथ संलग्न विवरणमा उल्लेख भए बमोजिमका मालसामानहरू आवश्यक भएको हुँदा यस स्थान(दुल्लू, दैलेख)सम्म के कति दररेटमा उपलब्ध गराउन सकिन्छ? प्रचलित बजारभाउमा नबढ्नेगरी सूचना प्रकाशित भएको मितिले ७(सात) दिन भित्र यस कार्यालयमा दररेट पेश गर्नुहुन अनुरोध छ।

५३०८ बुढा (क्षेत्री)
प्रमुख प्रशासकीय अधिकृत
पदम बुढा बुढा (क्षेत्री)
प्रमुख प्रशासकीय अधिकृत

| सि. नं. | सामानको विवरण | स्पेशिफिकेशन | प्रति एकाई दर(मु.अ. कर बाहेक) रु. |
|---------|---|--|-----------------------------------|
| १ | Mini Tiller- 3.2 kW to 3.9 kW (Diesel Engine) | Rated Power: 3.2 kW to 3.9 kW Rated Speed: 3600 rpm or more Engine type: Air cooled, Single cylinder, 4-Stroke engine Fuel Used: Diesel Starting System: Manual Recoil Start Fuel Tank Capacity: 2.5 L or more Bore×Stroke: At least of 73×59 mm Transmission Type: Full Gear Transmission Number of Speed: 2 Fwd., 1 Rev. Cultivator Width: 950 mm or more Cultivator Depth: 100 mm or more Number of blades: 24 tynes or more Warranty: Minimum one year service warranty is required | |



दुल्लू नगरपालिका
नगर कार्यपालिकाको कार्यालय



दुल्लू, देलेख
काभ्रेपञ्चनगरपालिका
२०७३

पत्र संख्या २०८२/०८३

चलानी नं. :-

| सि. नं. | सामानको विवरण | स्पेशिफिकेशन | प्रति एकाई दर(मु.अ. कर बाहेक) रु. |
|---------|---|---|-----------------------------------|
| २ | Mini Tiller- 4 kW to 5 kW (Diesel Engine) | Rated Power: 4 kW to 5 kW Rated Speed: 3600 rpm or more Engine type: Air cooled, Single cylinder, 4-Stroke engine Fuel Used: Diesel Starting System: Manual Recoil Start Fuel Tank Capacity: 3.5 L or more Bore×Stroke: At least of 78×62 mm Transmission Type: Full Gear Transmission Number of Speed: 2 Fwd., 1 Rev. Cultivator Width: 1050 mm or more Cultivator Depth: 100 mm or more Number of blades: 32 tynes or more Warranty: Minimum one year service warranty is required | |
| ३ | Mini Tiller- 3.2 kW to 3.9 kW (Petrol Engine) | Rated Power: 3.2 kW to 3.9 kW Rated Speed: 3200 rpm or more Engine type: Air cooled, Single cylinder, 4-Stroke engine Fuel Used: Petrol Starting System: Manual Recoil Start Fuel Tank Capacity: 2.5 L or more Transmission Type: Full Gear Transmission Number of Speed: 2 Fwd., 1 Rev. Cultivator Width: 850 mm or more Cultivator Depth: 80 mm or more Number of blades: 24 tynes or more Warranty: Minimum one year service warranty is required | |

५३०८८
पदम बहादुर बुढा (खेत्री)
मुख्य कार्यकारी अधिकृत



दुल्लू नगरपालिका
नगर कार्यपालिको कार्यालय



दुल्लू देलख
नगर कार्यपालिका
कोशी प्रदेश नेपाल
दुल्लू, देलख
२०७३

पत्र संख्या २०८२/०८३

चलानी नं :-

| सि. नं. | सामानको विवरण | स्पेशिफिकेशन | प्रति एकाई दर(मु.अ. कर बाहेक) रु. |
|---------|---|---|-----------------------------------|
| ४ | Mini Tiller- 4 kW to 5 kW (Petrol Engine) | Rated Power: 4 kW to 5 kW Rated Speed: 3200 rpm or more Engine type: Air cooled, Single cylinder, 4-Stroke engine Fuel Used: Diesel Starting System: Manual Recoil Start Fuel Tank Capacity: 3.0 L or more Transmission Type: Full Gear Transmission Number of Speed: 2 Fwd., 1 Rev. Cultivator Width: 900 mm or more Cultivator Depth: 100 mm or more Number of blades: 32 tynes or more Warranty: Minimum one year service warranty is required | |
| ५ | Electric Rice Combine Mill | Power Source: Single phase electric motor Matched Power: 2.0 kW to 2.5 kW Rotating Speed Motor: 2800 rpm or higher Rice Mill: Spindle Speed: 1200 rpm or higher Noise: <85 dB(A) Capacity: 150 Kg/h or higher Crusher (or Flour Mill): Spindle Speed: 4850 rpm or higher Noise: <85 dB(A) Capacity: 120 Kg/h or higher | |

५३०८८१
प्रदम बहादुर बुजा (क्षेत्री)
प्रमुख प्रशासकीय अधिकृत



दुल्लु नगरपालिका
नगर कार्यपालिको कार्यालय



दुल्लु नगरपालिका
कणाली प्रमुख नेपाल
२०७३

पत्र संख्या २०८२/०८३

चलानी नं :-

| सि. नं. | सामानको विवरण | स्पेशिफिकेशन | प्रति एकाई दर(मु.अ. कर बाहेक) रु. |
|---------|---|--|-----------------------------------|
| ६ | Multicrop Mini Thresher (Petrol Engine) | Machine Type: Petrol Multi-Crop Thresher Engine Power: 4.5 kW to 6.7 kW Engine type: Air cooled, Single cylinder, 4-Stroke engine Fuel Used: Petrol Starting System: Manual Recoil Start Fuel Tank Capacity: 3 to 5 L Threshing Drum: Adjustable speed, cylinder type Drum RPM: ~600 to 1,000 rpm Feeding Type: Manual feed hopper Threshing Cage: Removable/Changeable perforated concaves Crop Types: Paddy, wheat, maize, barley, millet, legumes Collection Method: Grain outlet + Chaff outlet Capacity: 200 to 500 kg/hour Warranty: Minimum one year brand/service warranty is required | |
| ७ | Brush Cutter | Mount Type: Backpack Engine Type: Single cylinder, 4-stroke, air-cooled Rated Power: 1.5 kW to 2 kW Fuel Used: Petrol Displacement: 45 to 60 cc Fuel Tank Capacity: 500 ml or more Blade Diameter/Size: 250 mm or more Cutting Speed: 6000 rpm or more | |

५४०२
पदम बहादुर मुद्ग (क्षेत्री)
प्रमुख प्रशासकीय अधिकृत



दुल्लु नगरपालिका
नगर कार्यपालिको कार्यालय



दुल्लु, कैलाली
कैलाली प्रदेश नेपाल
२०७३

पत्र संख्या २०८२/०८३

चलानी नं. :-

| सि. नं. | सामानको विवरण | स्पेशिफिकेशन | प्रति एकाई दर(मु.अ. कर बाहेक) रु. |
|---------|--------------------------|---|-----------------------------------|
| ८ | Laminar Air Flow Machine | Main Structure: More than 12 mm thick board with external Sunmica covering Workbench Surface: Stainless Steel (SS) Side Panels: Transparent Acrylic sheets Front Door: Collapsible Acrylic door Working Area Size: (60*60*60) cm / (90*60*60) cm / (120*60*60)cm / (180*60*60) cm Motor/Blower: At least 150 to 750 Watt electric motor with properly balanced blower HEPA Filter Efficiency: 99.97% efficiency for particles up to 0.03 micron Pre-Filter: Located at the bottom to supply pre-filtered air to blowers Lighting: At least One fluorescent tube for illumination Sterilization: At least One U.V. germicidal tube Monitoring: Static Pressure Manometer (fitted on top) Additional Fittings: Gas cock included Maintenance Access: Back cover fixed with screws for easy removal to service motor/filters Warranty: <i>Minimum one year brand/service warranty is required</i> | |
| ९ | Ridger for Mini Tiller | Material: Mild steel frame and wings Suitable for: 5 hp to 9 hp walk behind mini tiller Working Ridge Width: 15 cm to 50 cm Working Ridge Depth: 200 mm or less Weight: 3 kg to 7 kg Application: For row crops (potato, sugarcane, vegetables), hilly small plots, furrow/row formation | |

५३००८
पदम बहादुर बुढा (देउडा)
प्रमुख कार्यकारी अधिकृत



दुल्लू नगरपालिका
नगर कार्यपालिकाको कार्यालय



दुल्लू, देलेखे
कर्णाली प्रदेश, नेपाल
२०७३

पत्र संख्या २०८२/०८३

चलानी नं :-

| सि. नं. | सामानको विवरण | स्पेसिफिकेशन | प्रति एकाई दर(मु.अ. कर बाहेक) रु. |
|---------|--|--|-----------------------------------|
| १० | Silpaulin Plastic | Material: HDPE Plastic Colour: Standard Mass (Weight per unit area): 120 GSM Size (m2): 7 15 | |
| ११ | Drip irrigation Set for 6*12 m Polyhouse | Drip irrigation Set for 6*12 m Polyhouse (16 mm Main line pipe, 8 line 16 mm LLDPE drip pipes, 100 Ltr. water tank, screen filter) | |
| १२ | Electric Chaff Cutter | Body Material: Mild steel powder-coated for corrosion resistance Power source: Single phase electric motor Type: Portable Rated Power: 1.8 kW to 2.4 kW Rated Voltage: 200 V to 240 V Rated Speed: 900 rpm or higher Automation Grade: Semi-automatic Blade Material: High Carbon steel Shape of Moving Knife: Rectangular No. of moving blades: At least four Cutting Length/Size: Adjustable 5 – 50 mm (for fodder, straw, hay, sugarcane leaves, etc.) Feeding Type: Hopper feed with safety guard Hopper: Conveying belt should be provided in hopper for easy feeding Mobility: Wheels provided for portability Productivity: At least 350 kg/hr. Warranty: Minimum one year service warranty is required | |

५३०८२
पदम बहादुर मुन्ना (खेत्री)
मुख्य प्रशासकीय अधिकृत



दुल्लू नगरपालिका
नगर कार्यपालिका कार्यालय



दुल्लू, देलेख
कर्णाली प्रदेश नेपाल
२०७३

पत्र संख्या २०८२/०८३

चलानी नं :-

| सि. नं. | सामानको विवरण | स्पेसिफिकेशन | प्रति एकाई दर(मु.अ. कर बाहेक) रु. |
|------------|------------------------|---|--------------------------------------|
| १३ | Burdizzo Castrator | Type: Burdizzo (Bloodless) Material: Forged Steel/ Stainless Steel Handle: Long handle with non-slip grip Operation: Manual, blodless castration Available Sizes: 9"/ 12" Durability: Corrosion Resistant Weight: ≥ 1 Kg | |
| १४ | Feed Pellet Machine | Material of Construction: Carbon steel and Stainless steel Drive System: Direct motor drive / Gear-assisted Machine Type: Flat Die Feed Pellet Machine Power Consumption: ~2.2 to 3.7 kW Motor Type: Single-phase or Three- phase induction motor Voltage: 200 to 240 V (single phase); 50 Hz Operation Type: Semi-automatic Pelleting die size: 2-10 mm (Adjustable) Die Material: Alloy steel (heat-treated) Roller Material: Hardened steel Production Capacity: 60-80 kg/hour Machine Weight (approx.): ~80 to 120 kg Warranty: <i>Minimum one year brand/service warranty is required</i> | |
| १५ | Digital Balance-50 kg | Display: Digital Colour: Standard Range of Weight: 100 gm to 50 kg | |
| १६ | Digital Balance-100 kg | Display: Digital Colour: Standard Range of Weight: 100 gm to 100 kg | |

५३०८६
पद्म विहादर बुढा क्षेत्री
प्रमुख पञ्चासकी अधिकृत



दुल्लू नगरपालिका
नगर कार्यपालिको कार्यालय



दुल्लू, देलेख
कमलेश्वरी नगरपालिका
दुल्लू, देलेख
२०७३

पत्र संख्या २०८२/०८३

चलानी नं :-

| सि. नं. | सामानको विवरण | स्पेशिफिकेशन | प्रति एकाई दर(मु.अ. कर बाहेक) रु. |
|---------|--------------------|--|-----------------------------------|
| १७ | Incubator-528 Eggs | Conctruction Material: Insulated plastic/Metal housing Power Supply: AC 180 to 240 V, 50 Hz Power Consumption: 150 W to 500 W Display: Digital LED/LCD display for temp/humidity/time Control System: Digital microcomputer / PID controller Temperature Display Range: 0 to 40.5°C Temperature Measurement Precision: $\pm 0.1^\circ\text{C}$ Humidity Range: 0 to 99% RH (Display); Precise control $\pm 5\%$ RH Humidity Control: Microcomputer control/Automatic water refill Egg Turning: Fully automatic turning system (Programmable) Turning Cycle: Adjustable Ventilation: Controlled airflow system/Automatic exhaust fan Alarm System: Over-temp and humidity alarms Capacity: 528 chicken eggs or more Hatch Rate: ~95 to 98 % Weight (approx): ~60-80 Kg Applicable Eggs: Chicken, duck, goose, turkey, quail etc. Warranty: Minimum one year brand/service warranty is required | |

५८०२
पदवी नं. ३
मुख्य प्रशासकीय अधिकृत



दुल्ल नगरपालिका
नगर कार्यपालिको कार्यालय



दुल्ल नगरपालिका
कर्णाली प्रदेश नेपाल
२०७३

पत्र संख्या २०८२/०८३

चलानी नं :-

| सि. नं. | सामानको विवरण | स्पेशिफिकेशन | प्रति एकाई दर(मु.अ. कर बाहेक) रु. |
|------------|--------------------------------------|--|--------------------------------------|
| १८ | Incubator Machine-112 to 128 Eggs | Power Source: AC & DC both Power: 70 Watts (AC or DC) or more Required Voltage: AC 200 to 240 V; DC 12 V Colour: Standard Overall Size (L×B×H) (mm): (470 × 470 × 350) or more No. of Tray: Two Capacity: 112 to 128 eggs Egg Turner: Automatic Temperature Controller: Automatic Humidity Controller: Automatic Warranty: Minimum one year brand/service warranty is required | |

❖ नोट: कोटेशन पेश गर्दा मेसिनरी समग्री को प्रमाणित प्राविधिक Specification सहितको catalogue अनिवार्य पेश गर्नु पर्नेछ।

४३०५६
२०८२/१०/२३
www.dullu.gov.np
दुल्ल नगरपालिका अधिकार